



## APPLICATION

### ON-HIGHWAY, DRIVE-AXLE OPERATIONS

The TY303 is a deep tread, drive-axle workhorse for on-highway operations. Its advanced shoulder lug groove pattern promotes flat, even treadwear throughout the long life of the tire. The special tread compound extends tire mileage and precise casing construction allows excellent retreadability. The TY303 is ideal for 2- or 3-axle tractors and is available in low-profile sizes.

### FEATURES AND BENEFITS

- Special Tread Compound generates long, even tread life.
- Advanced Arrangement of Shoulder Lug Grooves promotes flat, even treadwear.
- Rib-block Tread Design provides outstanding traction on snow and muddy terrain and excellent durability.

TY303 replaces: **Michelin XDE-MS • Goodyear G622 RSD • Bridgestone M711**

TIRE SIZE	PART NUMBER	PLY RATING (L.R.)	TIRE WEIGHT (LBS)	RIM SIZE (INCH)		INFLATED DIMENSIONS		TREAD DEPTH (1/32")	LOADED DIMENSIONS		RPM	MAX LOAD CAPACITY AT COLD INFLATION PRESSURE				MAX SPEED (MPH)
				MEASURE	ALT	OVERALL WIDTH (INCH)	OVERALL DIAMETER (INCH)		SECTION WIDTH (INCH)	STATIC RADIUS (INCH)		LB/PSI SINGLE	LB/PSI DUAL	KB/KPA SINGLE	KB/KPA DUAL	
225/70R19.5	30319	12F	71.6	6.75	8.0	8.7	32	20	9.4	15.0	651	3640@95	3415@95	1650@660	1550@660	75
265/70R19.5	30315	14G	89.5	7.5	8.25	10.3	34.4	21	11.2	16.0	607	5070@110	4675@110	2300@760	2120@760	75
285/70R19.5	30316	16H	99.0	8.25	7.5 - 9.0	11.1	35.4	21	12.1	16.4	591	6395@120	6005@120	2900@830	2725@830	75
255/70R22.5	30312	16H	98.4	7.5	8.25	10	37	24	10.8	17.3	563	5510@120	5070@120	2500@830	2300@830	75